

```

<!-- edited with XMLSpy v2012 rel. 2 sp1 (x64) (http://www.altova.com) by Stefano (1)
-->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified" version="1.0">
  <xs:element name="Segnatura" type="SegnaturaType"/>
  <xs:complexType name="SegnaturaType">
    <xs:sequence>
      <xs:element name="Intestazione" type="IntestazioneType"/>
      <xs:element name="Documenti" type="DocumentiType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="IntestazioneType">
    <xs:sequence>
      <xs:element name="Oggetto" type="xs:string"/>
      <xs:element name="Flusso" type="FlussoType"/>
      <xs:element name="Mittenti" type="MittentiType" minOccurs="0"/>
      <xs:element name="Destinatari" type="DestinatariType" minOccurs="0"/>
      <xs:element name="Classifica" type="ClassificaType" minOccurs="0"/>
      <xs:element name="FascicoloPrimario" type="FascicoloType" minOccurs="0"/>
      <xs:element name="FascicoliSecondari" type="FascicoliSecondariType"
minOccurs="0"/>
      <xs:element name="Smistamento" type="SmistamentoType" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="SmistamentoType">
    <xs:sequence>
      <xs:element name="UnitaOrganizzativa" type="UnitaOrganizzativaType"
minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="Persona" type="PersonaType" minOccurs="0" maxOccurs=
"unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="FascicoliSecondariType">
    <xs:sequence>
      <xs:element name="FascicoloSecondario" type="FascicoloType" minOccurs="0"
maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="FascicoloType">
    <xs:sequence>
      <xs:element name="CodiceAmministrazione" type="xs:string"/>
      <xs:element name="CodiceAOO" type="xs:string"/>
      <xs:element name="Classifica" type="xs:string"/>
      <xs:element name="Anno" type="xs:int"/>
      <xs:element name="Progressivo" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ClassificaType">
    <xs:sequence>
      <xs:element name="CodiceAmministrazione" type="xs:string"/>
      <xs:element name="CodiceAOO" type="xs:string"/>
      <xs:element name="Classifica" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="DestinatariType">

```

```

<xs:sequence>
  <xs:element name="Destinatario" type="MittDestType" minOccurs="0" maxOccurs
    ="unbounded"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="MittentiType">
  <xs:sequence>
    <xs:element name="Mittente" type="MittDestType" minOccurs="0" maxOccurs=
      "unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="FlussoType">
  <xs:sequence>
    <xs:element name="TipoRichiesta" type="xs:string" minOccurs="0"/>
    <xs:element name="Firma" type="xs:string"/>
    <xs:element name="ForzaRegistrazione" type="xs:int"/>
    <xs:element name="Firmatario" type="FirmatarioType" minOccurs="0"/>
    <xs:element name="ProtocolloMittente" type="ProtocolloType" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ProtocolloType">
  <xs:sequence>
    <xs:element name="CodiceAmministrazione" type="xs:string" minOccurs="0"/>
    <xs:element name="CodiceAOO" type="xs:string" minOccurs="0"/>
    <xs:element name="Classifica" type="xs:string"/>
    <xs:element name="Data" type="xs:string" minOccurs="0"/>
    <xs:element name="Fascicolo" type="xs:string"/>
    <xs:element name="Numero" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="FirmatarioType">
  <xs:sequence>
    <xs:element name="Persona" type="PersonaType"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="MetadatiType">
  <xs:sequence>
    <xs:element name="Parametro" type="ParametroType" minOccurs="0" maxOccurs=
      "unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ParametroType">
  <xs:attribute name="nome" type="xs:string"/>
  <xs:attribute name="valore" type="xs:string"/>
</xs:complexType>
<!-- Destinatario -->
<xs:complexType name="MittDestType">
  <xs:sequence>
    <xs:choice>
      <xs:sequence>
        <xs:element name="Amministrazione" type="AmministrazioneType"/>
        <xs:element name="AOO" type="AOOType"/>
        <xs:element name="RiferimentiProtocollo" type="ProtocolloType"
          minOccurs="0"/>
      </xs:sequence>
    </xs:choice>
  </xs:sequence>

```

```

    <xs:sequence>
      <xs:element name="Denominazione" type="DenominazioneType" minOccurs
        ="0"/>
      <xs:element name="Persona" type="PersonaType" maxOccurs="unbounded"
        />
    </xs:sequence>
    <xs:element name="PersonaGiuridica" type="PersonaGiuridicaType"
      minOccurs="0"/>
  </xs:choice>
  <xs:element name="IndirizzoTelematico" type="IndirizzoTelematicoType"
    minOccurs="0"/>
  <xs:element name="Telefono" type="TelefonoType" minOccurs="0" maxOccurs=
    "unbounded"/>
  <xs:element name="Fax" type="FaxType" minOccurs="0" maxOccurs="unbounded"/>
  <xs:element name="IndirizzoPostale" type="IndirizzoPostaleType" minOccurs=
    "0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="AmministrazioneType">
  <xs:sequence>
    <xs:element name="Denominazione" type="DenominazioneType" minOccurs="0"/>
    <xs:element name="CodiceAmministrazione" type="CodiceAmministrazioneType"/>
    <xs:element name="IndirizzoTelematico" type="IndirizzoTelematicoType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="ForzaIndirizzoTelematico" type="xs:string" minOccurs="0"/>
    <xs:choice minOccurs="0">
      <xs:element name="UnitaOrganizzativa" type="UnitaOrganizzativaType"/>
      <xs:sequence>
        <xs:choice minOccurs="0">
          <xs:element name="Ruolo" type="RuoloType"/>
          <xs:element name="Persona" type="PersonaType"/>
        </xs:choice>
        <xs:element name="IndirizzoPostale" type="IndirizzoPostaleType"
          minOccurs="0"/>
        <xs:element name="Telefono" type="TelefonoType" minOccurs="0"
          maxOccurs="unbounded"/>
        <xs:element name="Fax" type="FaxType" minOccurs="0" maxOccurs=
          "unbounded"/>
      </xs:sequence>
    </xs:choice>
    <xs:element name="InvioPEC" type="InvioPECType" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="AOOType">
  <xs:sequence>
    <xs:element name="Denominazione" type="DenominazioneType" minOccurs="0"/>
    <xs:element name="CodiceAOO" type="CodiceAOOType"/>
    <xs:element name="IndirizzoTelematico" type="IndirizzoTelematicoType"
      minOccurs="0"/>
    <xs:element name="ForzaIndirizzoTelematico" type="xs:string" minOccurs="0"/>
    <xs:element name="InvioPEC" type="InvioPECType" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="DenominazioneType" mixed="true"/>
<xs:complexType name="CodiceAmministrazioneType" mixed="true"/>

```

```

<xs:complexType name="UnitaOrganizzativaType">
  <xs:sequence>
    <xs:element name="Denominazione" type="DenominazioneType" minOccurs="0"/>
    <xs:element name="Identificativo" type="IdentificativoType"/>
    <xs:choice minOccurs="0">
      <xs:element name="UnitaOrganizzativa" type="UnitaOrganizzativaType"/>
      <xs:sequence>
        <xs:choice minOccurs="0" maxOccurs="unbounded">
          <xs:element name="Ruolo" type="RuoloType"/>
          <xs:element name="Persona" type="PersonaType"/>
        </xs:choice>
        <xs:element name="IndirizzoPostale" type="IndirizzoPostaleType"
          minOccurs="0"/>
        <xs:element name="IndirizzoTelematico" type="
          IndirizzoTelematicoType" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="Telefono" type="TelefonoType" minOccurs="0"
          maxOccurs="unbounded"/>
        <xs:element name="Fax" type="FaxType" minOccurs="0" maxOccurs="
          unbounded"/>
      </xs:sequence>
    </xs:choice>
  </xs:sequence>
  <xs:attribute name="tipo" default="permanente">
    <xs:simpleType>
      <xs:restriction base="xs:NMTOKEN">
        <xs:enumeration value="temporanea"/>
        <xs:enumeration value="permanente"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
</xs:complexType>
<xs:complexType name="RuoloType">
  <xs:sequence>
    <xs:element name="Denominazione" type="DenominazioneType"/>
    <xs:element name="Identificativo" type="IdentificativoType" minOccurs="0"/>
    <xs:element name="Persona" type="PersonaType" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="PersonaType">
  <xs:sequence>
    <xs:element name="Identificativo" type="IdentificativoType" minOccurs="0"/>
    <xs:element name="Nome" type="NomeType" minOccurs="0"/>
    <xs:element name="Cognome" type="CognomeType" minOccurs="0"/>
    <xs:element name="Titolo" type="TitoloType" minOccurs="0"/>
    <xs:element name="IndirizzoTelematico" type="IndirizzoTelematicoType"
      minOccurs="0"/>
    <xs:element name="InvioPEC" type="InvioPECType" minOccurs="0"/>
    <xs:element name="IndirizzoPostale" type="IndirizzoPostaleType" minOccurs="
      0"/>
    <xs:element name="Denominazione" type="DenominazioneType" minOccurs="0"/>
    <xs:element name="CodiceFiscale" type="CodiceFiscaleType" minOccurs="0"/>
    <xs:element name="Metadati" type="MetadatiType" minOccurs="0"/>
  </xs:sequence>
  <xs:attribute name="id" type="xs:string" use="required"/>
</xs:complexType>

```

```

<xs:complexType name="IndirizzoPostaleType">
  <xs:choice>
    <xs:element name="Denominazione" type="DenominazioneType"/>
    <xs:sequence>
      <xs:element name="Toponimo" type="ToponimoType"/>
      <xs:element name="Civico" type="CivicoType"/>
      <xs:element name="CAP" type="CAPType"/>
      <xs:element name="Comune" type="ComuneType"/>
      <xs:element name="Provincia" type="ProvinciaType"/>
      <xs:element name="Nazione" type="NazioneType" minOccurs="0"/>
    </xs:sequence>
  </xs:choice>
</xs:complexType>
<xs:complexType name="IndirizzoTelematicoType" mixed="true">
  <xs:attribute name="tipo" use="optional" default="smtp">
    <xs:simpleType>
      <xs:restriction base="xs:NMTOKEN">
        <xs:enumeration value="uri"/>
        <xs:enumeration value="smtp"/>
        <xs:enumeration value="NMTOKEN"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute name="note" type="xs:anySimpleType"/>
</xs:complexType>
<xs:complexType name="TelefonoType" mixed="true">
  <xs:attribute name="note" type="xs:anySimpleType"/>
</xs:complexType>
<xs:complexType name="FaxType" mixed="true">
  <xs:attribute name="note" type="xs:anySimpleType"/>
</xs:complexType>
<xs:complexType name="IdentificativoType" mixed="true"/>
<xs:complexType name="NomeType" mixed="true"/>
<xs:complexType name="CognomeType" mixed="true"/>
<xs:complexType name="TitoloType" mixed="true"/>
<xs:complexType name="CodiceFiscaleType" mixed="true"/>
<xs:complexType name="ToponimoType" mixed="true">
  <xs:attribute name="dug" type="xs:anySimpleType"/>
</xs:complexType>
<xs:complexType name="CivicoType" mixed="true"/>
<xs:complexType name="CAPType" mixed="true"/>
<xs:complexType name="ComuneType" mixed="true">
  <xs:attribute name="codiceISTAT" type="xs:anySimpleType"/>
</xs:complexType>
<xs:complexType name="ProvinciaType" mixed="true"/>
<xs:complexType name="NazioneType" mixed="true"/>
<xs:complexType name="CodiceA00Type" mixed="true"/>
<xs:complexType name="InvioPECType" mixed="true"/>
<xs:complexType name="PersonaGiuridicaType">
  <xs:sequence>
    <xs:element name="Denominazione" type="DenominazioneType"/>
    <xs:element name="IndirizzoPostale" type="IndirizzoPostaleType" minOccurs="0"/>
    <xs:element name="IndirizzoTelematico" type="IndirizzoTelematicoType" minOccurs="0"/>
  </xs:sequence>

```

```

    <xs:element name="ForzaIndirizzoTelematico" type="xs:string" minOccurs="0"/>
    <xs:element name="InvioPEC" type="InvioPECType" minOccurs="0"/>
    <xs:element name="Metadati" type="MetadatiType" minOccurs="0"/>
  </xs:sequence>
  <xs:attribute name="tipo" type="xs:string" use="required"/>
  <xs:attribute name="id" type="xs:string" use="required"/>
</xs:complexType>
<xs:complexType name="DocumentoType">
  <xs:sequence>
    <xs:element name="Metadati" type="MetadatiType"/>
    <xs:element name="Acl" type="MetadatiType"/>
  </xs:sequence>
  <xs:attribute name="uri" type="xs:string" use="required"/>
  <xs:attribute name="id" type="xs:integer" use="required"/>
</xs:complexType>
<xs:complexType name="DocumentiType">
  <xs:sequence>
    <xs:element name="Documento" type="DocumentoType"/>
    <xs:element name="Allegati">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Documento" type="DocumentoType" minOccurs="0"
            maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Annessi">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Documento" type="DocumentoType" minOccurs="0"
            maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Annotazioni">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Documento" type="DocumentoType" minOccurs="0"
            maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```