



## LCD MONITOR

Display size	19" (48,26 cm)
Panel Type	Active Matrix TFT
Brightness	300 cd/m <sup>2</sup> (typ.)
Contrast	1000:1 (typ.)
Pixel pitch	0,294(H) x 0,294(V) mm
Resolution (H x V)	SXGA 1280 x 1024
Response time	5 ms (typ.)
View angles LR,UD	H/V 170°/160°
Display colors	16,2 Mio colors
Display Surface	Anti-Glare
Input 1	VGA, Audio
Input 2	DVI-D
Input 3	
Headphone	
Speakers	1W x 2
Supply	AC 100~240V, 50~60Hz
Consumption	37 W
Temperature	0 ~ 40°C
Humidity	10 ~ 90%
Dimension (W*D*H)	407 x 200 x 429 mm
Net weight	5.2 kg
Tilt	0° ~ 20°
Kensington Lock	✓
VESA mounting	VESA Standard, 100mm
On screen display	EN, SC, TC, DE, FR, IT, ES
Safety	BSMI, 3C, UL, TUV, CB, FCC, CE, TUV Ergonomie
Emission	TCO03
Power saving	EPA Energy Star
Extras 1	Height Adjustable
Extras 2	Pivot
Extras 3	
EAN	4710859552983
incl Accessory	powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card

© HANNSpree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.

The specifications are valid from production year 2008